



XSlite(SML830) is compact and robust 'Access and Time Attendance' system. In current scenario where security requirements are becoming stringent, we provide different access control and Identification systems to meet modern security needs. The systems are reliable, robust, easy to install with minimum support.



KEY FEATURES OF THE PRODUCT

- Card Buffer : 1000
- Event Buffer: 9999
- 4 doors can be configured with 8 IN/OUT Readers or 4 IN readers respectively.
- Can connect 8 controllers in a loop on TCP/IP network.
- User Friendly software with detailed attendance features.
- Supports HID, Mifare and EM cards.
- Advanced access control features like Anti-passback, Fire, Time Zones.

SPECIFICATIONS FOR SML830

■ SYSTEM FEATURES:

- **Storage Memory:** 8MB Flash
- **No. of Readers:** 8
- **Event Buffers:** 9999
- **Number of Users:** 1000
- **Readers Supported (Optional):** RS485 (Default)/ Wiegand (External 485 to Wiegand Converter)
- **Slave Id :** 8
- **Holiday Settings:** 16

■ ACCESS CONTROL FEATURES:

- **Exit Switch:** 4 (max)
- **Time Zone:** 16 (including 1 Free Time Zone)
- **Access Levels:** Unlimited
- **Inputs:** 4 i/p (Door Status, Egress)
- **Outputs:** 4 o/p (DOTL, Lock)
- **Antipass Back:** Available
- **Share Lock (IN/OUT)**

■ **HARDWARE FEATURES:**

- **LCD:** 16*2 alphanumeric
- **Output:** TCP/IP
- **Power:** Battery Backup Power Supply (DC 12V, Max. 2A for 8 Readers and Mother Board, 12 V 3 AMP for 4 Locks)
- **Color:** Siemens Grey.
- **Weight:** 2 kgs

■ **SOFTWARE:**

→ **smartENGINE Life Software.**

- Single location Software
- Advanced Shift Management and Attendance Features
- Access Control Configuration (Doors, Time Zones, Door Open Time, DOTL etc.)
- Cater the needs of Small & Single location offices
- Tally Payroll Interface payroll applications
- Indigenous Attendance software with various versions to cater various needs.

→ **Time Attendance Software**

- Time Attendance Software **smartSOFT™** Classic (Visit www.smartisystems.com for more details)
- Payroll Management Software.
- Third Party Software Integration is possible.

■ **DIMENSIONS:**

230 mm (L) X 295 mm (W) X 70 mm (D)

■ **COMMUNICATIONS:**

TCP/IP

■ **POWER SPECS:**

Current Req :
12V DC – 5 Amp

■ **ENCLOSURE:**

Siemens Grey Metal Enclosure

■ **MOUNTING:**

Wall Mounting

■ **PENDING CERTIFICATIONS:**

CE

■ **OPERATING TEMPERATURE:**

-10 deg C to + 60 deg C
10% to 90% Humidity

■ **WARRANTY:**

Product: 1 yr for any manufacturing defects / workmanship.

■ **ACCESSORIES (OPTIONAL):**

- Time Attendance Software
- 485 to Wiegand converter
- Strike Lock / Electromagnetic Lock
- Egress Switch
- 7 AH Battery

■ **APPLICATIONS:**

- Time Attendance System
- Physical Access Control

■ **BENEFITS:**

- Easy to configure and install
- User-friendly Remote Management System
- Metal Industrial Enclosure
- Compatible with HID Readers
- System Design Compatible to migrate legacy systems of similar Configuration

■ **AREAS:**

- Call Centers / BPO
- Banking & Finance
- Hotels and Residential
- Corporate & IT/ITES
- Retail, Malls & Multiplexes
- Hospitals & Clinics
- Clubs & Gymnasium
- Schools & Colleges
- Transport & Logistics
- Telecommunications
- R&D Centers and Labs
- Manufacturing Units & Factories,
- Government; PSU & Defense